

CHT Flooring Specifications as of December 30, 2014

Hardwood	Minimum 3/4" thickness. Gaps between boards to not exceed 0.025". Low or no VOC polyurethane. Please list the entire square footage
Engineered Wood	3 ply, 2 mm Wear Layer, at 20 year guarantee. http://www.hoskinghardwood.com/Department/Hardwood-Floors/All-About-Wear-Layers--Engineered-Flooring.aspx?dId=7&pageId=53
Laminate	Minimum 10mm thickness and 15 Year manufacturer Warranty. Please list the entire square footage measured for the quotation.
Vinyl Plank	6mm thickness, 10 mil wear layer. 20-year Residential Warranty.
Sheet Vinyl	20-year Residential Warranty
Shoe Mould	Include in quotation, measured length of shoe mould. Coordinating shoe mould around kitchen cabinets only: primed painted base shoe for remaining areas unless otherwise specified. Moulding that terminates at non-corner areas (e.g. at door-way trim) to be cut to 45 degrees unless otherwise specified
Underlayment	Include in quote if applicable, Standard underlayment as required by flooring warranty
Carpet	Minimum 10 Year warranty. Supplier/Retailer to specify & describe grade. "Berber" & "cut-loop" or similar recommended for high-traffic areas. Please list the entire square footage
Carpet Padding	Include in the quotation if applicable, standard padding as required by carpet warranty. 8 lb minimum.
Existing Flooring: Labor & Disposal	Include in the quotation if applicable, labor to remove and dispose of existing flooring: vinyl, tile, carpeting
Additional Labor	Include in the quotation if applicable, any labor to remove & re-install appliances, furniture, and plumbing fixtures (e.g. toilet)
Other	Include in the quotation in applicable, any upcharges for stairs/stairways, etc.